



FM8JN1D







Model		FM8JN1D-SGT					
Max. speed (Km/h)		103					
Gradeability % (Degre	e)	45.9 (24.6)					
Transmission model		M009 DD					
	Crawler	14.056					
	1st	9.647					
	2nd	6.993					
	3rd	5.021					
0	4th	3.636					
Gear ratio	5th	2.653					
	6th	1.923					
	7th	1.380					
	8th	1.000					
	Rev.	13.636					
Rear axle gear ratio		5.250					

ENGINE HINO J08E-WH

Max.output (EEC Net) 191 kW (260 PS)

at 2,500 rpm

Max.torque (EEC Net) 794 N.m (73 kgf.m)

at 1,500 rpm

Diesel 4-stroke cycle, Vertical 6 cylinder Type

In-line, Overhead camshaft, Water-cooled

Turbo intercooler

Fuel injection pump Electronic control, Commonrail type

Bore x Stroke 112 x 130 mm Piston displacement 7,684 cc Compression ratio 18.0:1 **Emission level** EURO 3

CLUTCH Dry single plate, Hydraulic control

> with air booster 9 Speeds, Direct drive

TRANSMISSION Synchromesh crawler - 8th

FRONT AXLE

Reverse elliot "I" section beam Type

Axle capacity 7,500 kg

REAR AXLE

Full-floating, Single reduction, Hypoid gearing Type

Axle capacity 21,000 kg

SERVICE BRAKE

Leading-trailing shoes operating by S-cam Type

shaft and slack adjuster acting on all wheels

Control Full air, Dual circuits

PARKING BRAKE

Wheel parking acting on front and R1 axle Type

EXHAUST BRAKE

Butterfly valve type Type

STEERING

Recirculating ball with hydraulic booster Type

Gear ratio 19.0

SUSPENSION

Front Semi-elliptic leaf springs with shock absorbers

Rear Semi-elliptic main with torque rods

WHEELS AND TIRES

Disc wheel 20 x 7.50, 10 studs Tire size 11.00-20-16 PR

FUEL TANK

390 L Capacity

CHASSIS FRAME

Ladder-shaped channel section side rails "]" Type

CAB

All steel welded construction, Laminated Type

safety glass applied

ELECTRICAL EQUIPMENT

12 V, 120 Ah. X 2 **Batteries** 24 V, 60 A Alternator

AIR CONDITIONER Denso

SAFETY SRS Airbag, Adjustable headlamp

Power window & Central lock COMFORTABILITY

PTO STANDARD EQUIPMENT

OPTION Wind deflector, ABS

Description			FM8JN1D-SGT				
Gross vehicle weight (GVW)		kg	25,000				
Chassis weight	Front	kg	3,160				
	Rear	kg	3,900				
	Total	kg	7,060				
Turning radius	Tire	mm	8,500				
Turning radius	Swept	mm	9,200				
Road clearance	At differential case	mm	245				
Number of seat			3				

DIMENSIONS										Unit: mm		
Model	Α	В	С	D	E	E'	F	G	Н	1	J	K
FM8JN1D-SGT	4,705	8,295	2,480	2,800	3,890	6,140	2,250	1,030	1,060	2,055	1,860	840

A - Wheelbase F - Rear overhang B - Overall length


C - Rear tire width


D - Overall height


E - Cab to rear axle

E' - Cab to end frame K - Chassis width

G - Frame height at front axle H - Frame height at rear axle I - Front tread J - Rear tread







Remark: HINO MOTORS SALES (Thailand) Ltd., has rights to change specifications without prior notice.



Hino Motors Sales (Thailand) Ltd. Tel. 0-2900-5000 Fax: 0-2900-5288 Hotline: 0-2305-4442 E-mail: info@hinothailand.com http://www.hinothailand.com













